Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-786-7510

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.555 inches **Overall Height:** Between 0.495 inches and 0.505 inches **Overall Width:** Between 0.182 inches and 0.197 inches **Mounting Hole Diameter:** Between 0.090 inches and 0.096 inches Shaft Diameter: Between 0.058 inches and 0.098 inches Shaft Length: Between 0.025 inches and 0.085 inches **Body Length:** Between 0.495 inches and 0.505 inches **Body Width:** Between 0.182 inches and 0.197 inches **Body Height:** Between 0.495 inches and 0.505 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 10.00 inch-ounces **Fragility Factor:** Moderately delicate Lateral Distance Between Mounting Hole Centers: Between 0.515 inches and 0.525 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

Electrical Resistance Per Section:

50.0 kilohms single section



NSN 5905-00-786-7510

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

7200.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0