NSN 5905-00-786-8572

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-786-8572

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.115 inches
Shaft Length:
0.050 inches
Body Length:
1.250 inches
Body Width:
0.280 inches
Body Height:
0.312 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.800 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
20.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

NSN 5905-00-786-8572

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-27208/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0