Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-786-9820

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Overall Length:**

1.313 inches

### **Body Diameter:**

0.875 inches

### Shaft Diameter:

0.125 inches

Shaft Length:

### 0.625 inches

### Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

0.688 inches

### Overall Diameter:

1.063 inches

# Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

### Actuator Type:

Single shaft

### Maximum Starting Torque:

6.00 inch-ounces

## Maximum Stop Torque:

80.00 inch-ounces

### Nonturn Device Location:

At 6 oclock

### Nonturn Device Radius:

0.250 inches

### Fragility Factor:

Moderately rugged

# Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0



**Terminal Location:** 

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

## **Features Provided:**

Humidity proof

### **Electrical Resistance Per Section:**

25.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

Between 290.0 and 305.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

### **Power Dissipation Rating Per Section In Watts:**

12.5 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 tab, solder lug

### **Specification Data:**

81349-mil-r-22/1 government specification

Shelf Life:

N/a

#### Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0