Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-787-4996

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Body Diameter:**

1.000 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.687 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

#### 0.469 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.438 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### Mounting Method:

Standard bushing

### **Electrical Resistance Per Section:**

100.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Standard Taper Curve Per Section:

A single section



### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0