

View Online at <https://aerobasegroup.com/nsn/5905-00-787-8936>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

2.8750 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

3.000 inches

Undercut Width:

0.0930 inches

Body Diameter:

3.000 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Body Length:

1.584 inches

Mounting Lip Diameter:

2.8750 inches

Mounting Lip Depth:

0.0730 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

358.0 and 350.0

Maximum Starting Torque:

1.90 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft End Play:

0.002 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.001 inches

Shaft Radial Play:

0.001 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

20.0 percent, rated amperes c and better

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Power Dissipation Rating Per Section In Watts:

4.0 7th secondary at 10'30 oclock

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

6 oclock all primaries

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

+0.0/+130.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0