## NSN 5905-00-789-5209

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-789-5209

13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
1.266 kilohms Resistance Tolerance In Percent: -1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+0.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.125 inches Body Longth: -0.250 inches Power Dissipation Rating In Watts: -0.250 inches Test Data Document: -13499-748-175-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing) specification, standard or other document that may be referenced in a basic governing drawing).	-8.0/+8.0 third temp coefficient
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+0.0 temp range of first temp coefficient in Deg Celsius: -65.0/+0.0 tem	Electrical Resistance:
-1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/40.0 temp range of first temp coefficient In Deg Celsius: -65.0/40.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 15499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) shelf-Life: Na Unit Of Measure: - Demilitarization: No Filg:	1.260 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+0.0 temp range of first temp coefficient Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/4.0.0 temp range of first temp coefficient Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established Body Dlameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the Dasic governing drawing), original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the Dasic governing drawing), original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  — Demilitarization:  No  Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+0.0 temp range of first temp coefficient InClosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating in Watts: 0.050 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Na  Unit Of Measure:  -  Demilitarization:  No  Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+0.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+0.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing trawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-65.0/+0.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:  Via Unit Of Measure:  Demilitarization: No Flig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Axial terminal each end Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-65.0/+0.0 temp range of first temp coefficient
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Encapsulated
Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fig:	Terminal Type:
Not established  Body Diameter: 0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Wire lead
Body Diameter:  0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing) etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fig:	Reliability Indicator:
0.125 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator: Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Not established
Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.050 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
0.250 inches  Power Dissipation Rating In Watts: 0.050 free air  Style Designator:  Axial terminal each end  Test Data Document: 13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.125 inches
Power Dissipation Rating In Watts:  0.050 free air  Style Designator:  Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
O.050 free air  Style Designator: Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 inches
Style Designator:  Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.050 free air
Test Data Document:  13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	13499-748-1775-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 13499-748-1809-00
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any
N/a Unit Of Measure: Demilitarization: No Fiig:	specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0