## NSN 5905-00-789-5867

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-789-5867 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 2.104 inches and 2.185 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.594 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** Between 1.448 inches and 1.466 inches **Overall Diameter:** 1.062 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3610.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.003 inches

Pilot Diameter Runout:
0.003 inches

## NSN 5905-00-789-5867

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Power Dissipation Rating Per Section In Watts:
1.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
+0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Peak noise 100mv
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-00-789-5867

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0