

View Online at <https://aerobasegroup.com/nsn/5905-00-789-5927>

**Section Quantity:**

7

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.9688 inches

**Pilot Length:**

0.0620 inches

**First Flat Length:**

0.377 inches

**Flat Height:**

Between 0.104 inches and 0.106 inches

**Undercut Diameter:**

0.969 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

Between 0.1242 inches and 0.1247 inches

**Shaft Length:**

0.437 inches

**Body Length:**

1.880 inches

**Mounting Lip Diameter:**

1.0620 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

7.5 percent, rated amperes c and better v.G. Stepping

**Function Conformity Tolerance Per Section:**

-1.50/+1.50 6th section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Function Conformity Per Section:**

All sections absolute conformity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Function Characteristic Per Section:**

All sections equation

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 all sections

**Test Data Document:**

97942-577r900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

30 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0