Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-789-5932

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.587 inches

#### Terminal Length:

0.187 inches

#### **Overall Height:**

0.405 inches

## Overall Width:

0.185 inches

#### Mounting Hole Diameter:

## 0.077 inches

Body Length:

#### 0.405 inches

**Body Width:** 

#### 0.185 inches

## Body Height:

0.405 inches

#### Actuator Type:

Flush drive with slot-hole

## Center To Center Distance Between Terminals:

0.200 inches

## Lateral Distance Between Mounting Hole Centers:

0.375 inches

## **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Upper adjacent side two rows

# Mounting Method:

Unthreaded hole

## Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

25.0 kilohms single section

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# NSN 5905-00-789-5932 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

#### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A002a0