NSN 5905-00-789-5982

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-789-5982



Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.250 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.025 inches **Mounting Bushing Length:** 0.292 inches **Body Length:** 1.137 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 16200.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

180.0 single section

NSN 5905-00-789-5982

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0