NSN 5905-00-789-7032

Nonprecision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-789-7032

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.625 inches
Shaft Length:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Electrical Resistance Per Section:
1.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
2.0 free air single section Resistance Tolerance Per Section In Percent:
•
Resistance Tolerance Per Section In Percent:
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section:
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life:
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life: N/a
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life: N/a
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life: N/a Unit Of Measure:
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life: N/a Unit Of Measure: Demilitarization:
Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Standard Taper Curve Per Section: A single section Shelf Life: N/a Unit Of Measure: Demilitarization: No