NSN 5905-00-790-0103

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-790-0103 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3120 inches Pilot Length: 0.1320 inches **Undercut Diameter:** 1.312 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.437 inches **Shaft Diameter:** 0.1249 inches **Shaft Length:** 0.620 inches **Body Length:** 2.250 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft End Play:** 0.00250 inches

Shaft Runout: 0.001 inches

NSN 5905-00-790-0103

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00150 inches
Shaft Radial Play:
0.002 inches
Ferminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
75.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
05.0 single section
Power Dissipation Rating Per Section In Watts:
2.5 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
5 single section
Tap Location Tolerance Per Section:
1.0/+1.0 ohms single section
Resistance Tolerance Per Section In Percent:
1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
5000.0 single section and 10000.0 single section and 15000.0 single section and 20000.0 single section and 25000.0 single section and
30000.0 single section and 35000.0 single section and 40000.0 single section and 45000.0 single section and 50000.0 single section and
55000.0 single section and 60000.0 single section and 65000.0 single section and 70000.0 single section and 75000.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Init Of Massura:

.

Demilitarization:

NSN 5905-00-790-0103

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0