NSN 5905-00-790-0113

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-790-0113 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.938 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.376 inches **Body Length:** 2.500 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style: Contact Arm Electrical Off Position:** Fully ccw-cw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:**

0.60 inch-ounces

0.50 inch-ounces

Maximum Running Torque:

NSN 5905-00-790-0113

Maximum Stop Torque:

Precision Nonwire Wound Variable Resistor - Page 2 of 3



80.00 inch-ounces
Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
1800.0 single section
Rotary Actuator Travel In Angular Deg:
3780.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-0.15/+0.15 ohms single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
2500.0 single section

25.0 single section

Single section linear

Function Characteristic Per Section:

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

NSN 5905-00-790-0113

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0