NSN 5905-00-790-0114

Precision Wire Wound Variable Resistor - Page 1 of 3

View Online at https://aerobasegroup.com/nsn/5905-00-790-0114



Section Quantity: Body Style: Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: Between 0.0590 inches and 0.0650 inches **Overall Length:** 2.500 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** Between 0.0590 inches and 0.0650 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.438 inches **Body Length:** 0.250 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** Between 0.0590 inches and 0.0650 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:**

0.60 inch-ounces

NSN 5905-00-790-0114

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Running Torque:
0.50 inch-ounces
Maximum Stop Torque:
5.00 inch-ounces
Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Pilot Diameter Runout:
0.010 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1260.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-790-0114

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0