

View Online at <https://aerobasegroup.com/nsn/5905-00-790-0114>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

Between 0.0590 inches and 0.0650 inches

**Overall Length:**

2.500 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

Between 0.0590 inches and 0.0650 inches

**Body Diameter:**

1.125 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.438 inches

**Body Length:**

0.250 inches

**Overall Diameter:**

0.875 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

Between 0.0590 inches and 0.0650 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

1080.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Maximum Running Torque:**

0.50 inch-ounces

**Maximum Stop Torque:**

5.00 inch-ounces

**Shaft End Play:**

0.001 inches

**Shaft Runout:**

0.001 inches

**Pilot Diameter Runout:**

0.010 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

1260.0

**Function Conformity Tolerance Per Section:**

-0.15/+0.15 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

80.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0