NSN 5905-00-791-2096

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-791-2096

Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 100.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Not established Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Body Diameter: 0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
0.250 inches Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Body Length: 0.625 inches Power Dissipation Rating In Watts: 3.000 free air
0.625 inches Power Dissipation Rating In Watts: 3.000 free air
Power Dissipation Rating In Watts: 3.000 free air
3.000 free air
Style Designator:
, ,
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0