

View Online at https://aerobasegroup.com/nsn/5905-00-791-5655

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.3120 inches

Pilot Length:

0.1320 inches

Overall Length:

3.704 inches

Undercut Diameter:

1.312 inches

Undercut Width:

0.0780 inches

Body Diameter:

0.975 inches

Shaft Diameter:

0.1874 inches

Shaft Length:

0.556 inches

Body Length:

3.000 inches

Overall Diameter:

1.437 inches

Mounting Lip Diameter:

1.4370 inches

Mounting Lip Depth:

0.0920 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

80.00 inch-ounces



Shaft Runout: 0.001 inches Lateral Runout: 0.001 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 5.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 3780.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 all sections Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections **Power Dissipation Rating Per Section In Watts:** 0.5 free air all sections **Function Conformity Per Section:** All sections absolute linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 all sections **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 80.0 all sections **Test Data Document:** 10001-2134444 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 screw Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

Fiig:

A002a0