NSN 5905-00-791-9886

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-791-9886

Seedien Overstitus
Section Quantity:
Reliability Indicator: Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
1.750 inches
Shaft Style:
Round
Actuator Type:
Dual concentric
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better industrial clears
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 2nd section
Special Features:
At a predetermined point, both wiperswith the resistance element to within porm 1 degree
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a

NSN 5905-00-791-9886

Precision Wire Wound Variable Resistor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A002a0