## NSN 5905-00-792-2990

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-792-2990

Section Quantity:
1
Reliability Indicator:
Not established
Overall Width:
0.375 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.375 inches
Overall Diameter:
0.750 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
4.00 inch-ounces
Maximum Running Torque:
4.00 inch-ounces
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
1
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Function Conformity Per Section:
Single section independent linearity

## NSN 5905-00-792-2990

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resi	istance	Tolerance	Per	Section	ln	Percent:

-5.0/+5.0 single section

**Terminal Type And Quantity:** 

3 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0