NSN 5905-00-792-7499

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-792-7499 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.313 inches **Overall Height:** Between 0.796 inches and 0.828 inches **Overall Width:** Between 0.270 inches and 0.290 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.094 inches and 0.125 inches **Shaft Length:** 0.063 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.270 inches and 0.290 inches **Body Height:** Between 0.796 inches and 0.828 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:**

9000.0 **Maximum Starting Torque:** 7.50 inch-ounces **Fragility Factor:** Moderately delicate **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 4 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

NSN 5905-00-792-7499

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
4002a0