NSN 5905-00-792-8444

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-792-8444

Section Quantity:

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.8750 inches
Pilot Length:
0.0620 inches
Overall Length:
3.312 inches
Undercut Diameter:
1.812 inches
Undercut Width:
0.0620 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.500 inches
Body Length:
1.781 inches
Overall Diameter:
2.469 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0930 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.75 inch-ounces
Maximum Running Torque:
0.75 inch-ounces

Fragility Factor:
Moderately rugged

NSN 5905-00-792-8444

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3785.0
Function Conformity Tolerance Per Section:
-0.005/+0.005 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1250.0/+1250.0 ohms single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tap Location From Ccw Terminal Per Section In Ohms:
25000.0 single section
Function Characteristic Per Section:
Single section graph
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
80.0 single section
Test Data Document:
37695-227880 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: