NSN 5905-00-793-9011

Composition Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-793-9011

Specification Data: 81349-mil-r-11/6 government specification Shelf Life:		
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: Bi349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	Resistance:	
-5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	ns	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	Tolerance In Percent:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	00	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	empurature In Deg Celsius At Full Rated Power:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:		
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	empurature In Deg Celsius At Zero Percent Rated Power:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:		
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	Method:	
Wire lead Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	ed	
Reliability Indicator: Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification depreciated programment and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	уре:	
Not established Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:		
Body Diameter: 0.225 inches Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	Indicator:	
Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	shed	
Body Length: 0.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	leter:	
O.562 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	es s	
Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	th:	
1.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	es s	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	sipation Rating In Watts:	
Axial terminal each end Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	air	
Test Data Document: 81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	gnator:	
81349-mil-r-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	al each end	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	Document:	
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-11/6 government specification Shelf Life: N/a	-11/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for	ormat
Specification Data: 81349-mil-r-11/6 government specification Shelf Life:	ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment	tal
81349-mil-r-11/6 government specification Shelf Life:	nance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	on Data:	
	-11/6 government specification	
N/a		
Unit Of Measure:	asure:	
		
Demilitarization:	ation:	
No		
Fiig:		
A001a0		