## NSN 5905-00-794-2399

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-794-2399 **Section Quantity:** 3 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.550 inches First Flat Length: 0.375 inches Flat Height: 0.109 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.800 inches **Overall Diameter:** 1.202 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 

0.312 inches

Shaft End Play:

0.005 inches

## NSN 5905-00-794-2399

**Shaft Runout:** 0.001 inches

9 turret

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Power Dissipation Rating Per Section In Watts:
1.2 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:

## NSN 5905-00-794-2399

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0