NSN 5905-00-794-3003

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-794-3003 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Shaft Diameter:** 0.200 inches **Shaft Length:** 0.400 inches **Body Length:** 0.500 inches **Body Width:** 0.100 inches **Body Height:** 0.150 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 Fragility Factor: Moderately delicate **Terminal Location:** Rear end **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section

Clutch

Actuator Travel Control Feature:

NSN 5905-00-794-3003

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature	In Deg Celsius	Per Section At	t Full Rated Power:
---------------------	----------------	----------------	---------------------

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0