## NSN 5905-00-794-3199

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-794-3199 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 1.172 inches **Body Width:** 0.969 inches **Body Height:** 0.500 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Terminal Location:** Lower adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 50.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -1000.0 to 1000.0 single section **Power Dissipation Rating Per Section In Watts:** 0.167 free air all sections **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** M single section **Terminal Type And Quantity:** 3 tab, solder lug

N/a

Shelf Life:

## NSN 5905-00-794-3199

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0