## NSN 5905-00-796-4627

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-796-4627

Section Quantity:
1
Body Style:
Cylindrical hole/slot mounted
Reliability Indicator:
Not established
Overall Length:
2.250 inches
Body Diameter:
3.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Body Length:
1.500 inches
Overall Diameter:
3.188 inches
Mounting Hole/stud Circle Diameter:
1.000 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
357.0
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
1.4 kilohms single section

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:** 

120.0 single section

NSN 5905-00-796-4627 Precision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
7.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Гар Location Tolerance Per Section:
0.5/+0.5 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0