Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-797-8781

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.500 inches

#### Shaft Diameter:

0.125 inches

Shaft Length:

0.375 inches

Mounting Bushing Length:

0.250 inches

#### Body Length:

# 0.406 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.188 inches

#### Screw Thread Diameter:

0.250 inches

**Screw Thread Series Designator:** 

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

3.0 megohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

0.25 free air single section

# Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

## Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A002a0