

View Online at <https://aerobasegroup.com/nsn/5905-00-797-9729>

Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

Reliability Indicator:

Not established

Body Diameter:

0.750 inches

Mounting Hole Diameter:

0.135 inches

Body Length:

0.375 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

220.0

Nonturn Device Location:

At 4'30 oclock

Nonturn Device Radius:

0.344 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

50.0 ohms single section

Rotary Actuator Travel In Angular Deg:

220.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Provision is made for screwdriver operation by a slot in the drive plate

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0