NSN 5905-00-798-2060

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-798-2060 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.469 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

NSN 5905-00-798-2060

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No