## NSN 5905-00-798-5598

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-798-5598 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.000 inches **Body Diameter:** 1.500 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** 1.000 inches **Body Length:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 40.0 **Mounting Facility Quantity: Terminal Location:** Rear-bottom **Mounting Method:** Threaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

## NSN 5905-00-798-5598

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
0.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No