Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-799-3683

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Body Diameter:**

1.156 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

# 0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Fragility Factor:

Moderately rugged

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### Terminal Location:

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

50.0 kilohms single section

## Power Dissipation Rating Per Section In Watts:

1.12 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### **Terminal Type And Quantity:**

3 tab, solder lug

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0