NSN 5905-00-799-3690

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-799-3690

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.250 inches
Body Diameter:
1.125 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.562 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:

360.0

NSN 5905-00-799-3690

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

