NSN 5905-00-799-9618

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-799-9618 **Section Quantity:** 1 **Body Style:** Cylindrical tab/flange mounted **Reliability Indicator:** Not established **Body Diameter:** 0.715 inches **Mounting Hole Diameter:** 0.078 inches **Body Length:** 0.380 inches **Actuator Type:** Flush drive with slot-hole **Lateral Distance Between Mounting Hole Centers:** 1.030 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Right-left adjacent sides **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 680.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -15.0 to 15.0 single section **Actuator Travel Control Feature:** Continuous motion **Standard Taper Curve Per Section:** A single section Removable shaft 7.562 in. Lg, 0.125 in. Dia, held by 4-40 unc-3a set screw

Special Features: Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

NSN 5905-00-799-9618

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demi			

No

Fiig:

A002a0