Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Grou

View Online at https://aerobasegroup.com/nsn/5905-00-801-1661

Section Quantity:

2

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.030 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.312 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

9000.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0