

View Online at <https://aerobasegroup.com/nsn/5905-00-801-5193>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Overall Length:**

1.300 inches

**Terminal Length:**

6.000 inches

**Overall Height:**

Between 0.290 inches and 0.310 inches

**Overall Width:**

Between 0.170 inches and 0.190 inches

**Mounting Hole Diameter:**

0.086 inches

**Shaft Diameter:**

Between 0.110 inches and 0.130 inches

**Shaft Length:**

Between 0.040 inches and 0.060 inches

**Body Length:**

Between 1.240 inches and 1.260 inches

**Body Width:**

Between 0.170 inches and 0.190 inches

**Body Height:**

Between 0.290 inches and 0.310 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

8.00 inch-ounces

**Lateral Distance Between Mounting Hole Centers:**

Between 0.995 inches and 1.005 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

2.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

7920.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

175.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0 to 70.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0