## NSN 5905-00-801-7832

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-801-7832

+55.0/+105.0  Electrical Resistance: 2.641 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:
2.641 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:
Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:
-0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power:
Ambient Tempurature In Deg Celsius At Full Rated Power:
00.0
66.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
121.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
+0.0/+60.0
Inclosure Method:
Hermetically sealed
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Body Diameter:
0.375 inches
Body Length:
1.000 inches
Power Dissipation Rating In Watts:
0.250 free air
Style Designator:
Axial terminal each end
Test Data Document:
64959-ga10684 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0