NSN 5905-00-802-3654

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-802-3654

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.062 inches
Shaft Diameter:
0.250 inches
Shaft Length: 0.375 inches
Mounting Bushing Length: 0.250 inches
Body Length:
1.594 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
820.0 ohms all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:

A all sections

NSN 5905-00-802-3654

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0