## NSN 5905-00-803-3450

**Section Quantity:** 

Cylindrical bushing mounted

Between 0.484 inches and 0.516 inches

Reliability Indicator:

Not established

Overall Length:

1.313 inches

Body Diameter:

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-803-3450

Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.609 inches and 0.641 inches
Mounting Bushing Length:
Between 0.484 inches and 0.516 inches
Body Length:
0.453 inches
Overall Diameter:
Between 0.484 inches and 0.516 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Radius:
Between 0.234 inches and 0.266 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
100.0 ohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

## NSN 5905-00-803-3450

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0