NSN 5905-00-803-4557

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-803-4557 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Body Length:** 0.500 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method: Terminal Electrical Resistance Per Section:** 500.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5905-00-803-4557

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0