## NSN 5905-00-803-4730

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-803-4730 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.938 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.453 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft

**Electrical Resistance Per Section:** 

2.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

## NSN 5905-00-803-4730

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 1.0 free air single section Resistance Tolerance Per Section In Percent: -20.0 to 20.0 single section Actuator Travel Control Feature: Stops Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A002a0