## NSN 5905-00-803-4731

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-803-4731

Section Overtitus
Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:  Not established
Body Diameter:
1.562 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.687 inches
Body Length:
1.375 inches
Overall Diameter:
1.719 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
750.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

## NSN 5905-00-803-4731

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0