NSN 5905-00-804-0745

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-804-0745

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Any acceptable
Pilot Length:
Any acceptable
Undercut Diameter:
Any acceptable
Undercut Width:
Any acceptable
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.313 inches
Body Length:
1.636 inches
Mounting Lip Diameter:
Any acceptable
Mounting Lip Depth:
Any acceptable
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
75.000 kilohms single section
Function Conformity Tolerance Per Section:
-0.25 to 0.25 single section

1.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-804-0745

Precision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section	ion Conformity Per	Section:
---------------------------------	--------------------	----------

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0