## NSN 5905-00-804-4276



View Online at h	https://aerobasegroup.com/nsn/5905-00-804-4276
Section Quanti	ty:
1	
Body Style:	
Cylindrical bush	ing mounted
Reliability Indi	cator:
Not established	
Overall Length	:
Between 1.687	inches and 1.937 inches
Body Diameter	:
Between 1.032	inches and 1.156 inches
Shaft Diameter	:
Between 0.248	inches and 0.251 inches
Shaft Length:	
Between 1.219	inches and 1.281 inches
Mounting Bush	ning Length:
Between 0.344	inches and 0.390 inches
Body Length:	
Between 0.468	inches and 0.656 inches
Overall Diamet	er:
1.515 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Maximum Star	ing Torque:
6.00 inch-ounce	s
Maximum Stop	Torque:

128.00 inch-ounces

**Nonturn Device Location:** 

At 9 oclock

**Nonturn Device Radius:** 

Between 0.515 inches and 0.547 inches

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-00-804-4276

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 309.0 and 320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/5 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: