NSN 5905-00-805-3430

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-805-3430

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.320 inches
Terminal Length:
0.500 inches
Overall Height:
0.810 inches
Overall Width:
0.180 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.110 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.180 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.080 inches and 0.100 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole

NSN 5905-00-805-3430 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Senter To Center Distance Between Terminal Rows:
0.070 inches
Electrical Resistance Per Section:
00.0 ohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
75.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
B pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
N002a0