Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-805-5642

## Section Quantity:

2

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

### **Pilot Diameter:**

1.3125 inches

#### **Pilot Length:**

0.0620 inches

#### **Overall Length:**

2.1562 inches

#### **Undercut Diameter:**

1.312 inches

#### **Undercut Width:**

### 0.0730 inches

**Body Diameter:** 

1.438 inches

#### Shaft Diameter:

0.250 inches

## Shaft Length:

0.6562 inches

## Body Length:

1.500 inches

### **Overall Diameter:**

1.4375 inches

### Mounting Lip Diameter:

1.4385 inches

### Mounting Lip Depth:

0.0620 inches

#### Shaft Style:

Round, slotted, undercut

### Shaft Bearing Type:

Ball

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

# Maximum Starting Torque:

0.95 inch-ounces

# Maximum Running Torque:

0.65 inch-ounces



# Shaft End Play: 0.00500 inches Shaft Runout: 0.002 inches Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.00200 inches Shaft Radial Play: 0.004 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 15.0 percent, rated amperes c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 all sections **Power Dissipation Rating Per Section In Watts:** 2.75 free air all sections **Function Conformity Per Section:** All sections independent linearity **Fixed Tap Quantity Per Section:** 3 2nd section **Tap Location Tolerance Per Section:** -1.0/+1.0 ohms all sections **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 all sections **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 7000.0 2nd section and 10500.0 2nd section and 14000.0 2nd section **Function Characteristic Per Section:** All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections **Terminal Type And Quantity:**

10 turret

# Shelf Life:

N/a

Precision Wire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0