## NSN 5905-00-806-2329

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-806-2329

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.087 inches
Shaft Diameter:
0.110 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.220 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70 0/±70 0 single section

0.5 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-00-806-2329

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0