

View Online at https://aerobasegroup.com/nsn/5905-00-806-2847

# Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

1.060 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.688 inches

## Mounting Bushing Length:

0.312 inches

## Body Length:

# 1.190 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

312.0

#### Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

9.0 kilohms all sections

# Rotary Actuator Travel In Angular Deg:

312.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

# NSN 5905-00-806-2847 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

# Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

## Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A002a0