

View Online at <https://aerobasegroup.com/nsn/5905-00-807-4123>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

Between 0.484 inches and 0.516 inches

Overall Height:

0.876 inches

Overall Width:

0.300 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

0.093 inches

Shaft Length:

0.030 inches

Body Length:

1.340 inches

Body Width:

0.300 inches

Body Height:

0.360 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Maximum Starting Torque:

7.50 inch-ounces

Center To Center Distance Between Terminals:

0.900 inches

Fragility Factor:

Moderately rugged

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0