Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-807-7079

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Overall Length:**

2.625 inches

#### Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

2.000 inches

#### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.625 inches

#### **Overall Diameter:**

1.453 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

100.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section



Power Dissipation Rating Per Section In Watts:

2.25 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

C single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0