NSN 5905-00-807-7656

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-807-7656

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.625 inches
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
2.000 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Overall Diameter:
1.453 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Electrical Resistance Per Section:
500.0 kilohms single section
Power Dissipation Rating Per Section In Watts:

2.0 free air single section

NSN 5905-00-807-7656

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



R	esistance	Tolerance	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0